

Rseries 端子形状 BL/SSはラグ端子板

单相 複巻



R1 100・110V-5~24V

品番	仕様			端子形状	外形寸法 (mm)				取付寸法 (mm)			取付穴 (mm)		端子種類	絶縁	重量	本体価格
	1次電圧	2次電圧	容量		W	D	H	I	A	B	C	E	F				
◎ R1-631	100V-0	6.3V	1A	BL	51	40	41	70	60			4×6		ラグ	A	約260g	
R1-632	110V 100V	5V	2A	BL	60	45	51	84	71			4×7		ラグ	A	約440g	
R1-633	0	0	3A	BL	69	50	59	91	80			4.5×6		ラグ	A	約740g	
◎ R1-1203	100V	12V・10V-0	0.3A	BL	43	36	36	60	51			3.8×4		ラグ	A	約150g	
◎ R1-1205	0	12V	0.5A	BL	51	40	41	70	60			4×6		ラグ	A	約260g	
◎ R1-121	110V	10V	1A	BL	60	45	51	80	70			4×6		ラグ	A	約450g	
◎ R1-122	100V	8V	2A	BL	69	55	59	91	80			4.5×6		ラグ	A	約770g	
R1-123	0	6V	3A	BL	79	65	67	104	92			4.5×8		ラグ	A	約1.2kg	
R1-125	0	0	5A	BL	79	75	67	104	92			4.5×7		ラグ	A	約1.6kg	
◎ R1-2003	110V	20V	0.3A	BL	51	40	41	70	60			4×6		ラグ	A	約260g	
◎ R1-2005		18V	0.5A	BL	60	45	51	80	70			4×6		ラグ	A	約440g	
◎ R1-201	100V	16V	1A	BL	69	55	59	91	80			4.5×6		ラグ	A	約770g	
R1-202		14V	2A	BL	79	65	67	104	92			4.5×8		ラグ	A	約1.2kg	
R1-203	0	0	3A	BL	79	80	67	104	92			4.5×7		ラグ	A	約1.6kg	
R1-205	0	0	5A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg	
◎ R1-2405	110V	24V	0.5A	BL	60	53	51	84	70			4×6		ラグ	A	約500g	
◎ R1-241		20V	1A	BL	69	59	59	91	80			4.5×6		ラグ	A	約900g	
◎ R1-242	100V	15V	2A	BL	79	70	67	104	92			4.5×6		ラグ	A	約1.4kg	
R1-243		12V	3A	BL	89	77	76	115	102			4.5×6		ラグ	A	約2.0kg	
R1-245	0	0	5A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg	


R1 100・110V-15~50V

◎ R1-3005	110V	30V	0.5A	BL	60	53	51	84	72			4×7		ラグ	A	約500g	
◎ R1-301		25V	1A	BL	69	65	60	94	80			4.5×6		ラグ	A	約1.0kg	
R1-302	100V	20V	2A	BL	79	75	67	104	92			4.5×7		ラグ	A	約1.6kg	
R1-303	0	15V	3A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg	
R1-3805	110V	38V	0.5A	BL	69	55	60	90	80			4.5×6		ラグ	A	約900g	
R1-381		35V	1A	BL	79	65	67	104	92			4.5×8		ラグ	A	約1.2kg	
R1-382	100V	32V	2A	BL	89	77	76	115	102			4×8		ラグ	A	約2.0kg	
R1-383	0	24V	3A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg	
◎ R1-501	110V	50V	1A	BL	79	70	67	104	92			4.5×6		ラグ	A	約1.4kg	
R1-502		45V	2A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg	
R1-503	100V	40V	3A	SS	96	95	82		59	67	40	5.5×10	4	ラグ	A	約2.9kg	


◎ 在庫品 ○ 非在庫品 無印 受注生産品

形状・寸法図


BL形 (ラグ端子板)



SS形 (ラグ端子板)



結線図



Rseries

端子形状 BL/SSIはラグ端子板 UPはIP2X対応ねじアップ式フィンガープロテクト端子台

単相 複巻



R2 200-220V-6~24V

品番	仕様			端子形状	外形寸法 (mm)				取付寸法 (mm)			取付穴 (mm)		端子	絶縁種類	重量	本体価格	
	1次電圧	2次電圧	容量		W	D	H	I	A	B	C	E	F					
○ R2-6305	220V-0	6.3V 0	0.5A	BL	43	36	35	60	52				3.8×4		ラグ	A	約160g	
○ R2-631	220V		1A	BL	51	40	41	70	60				4×6		ラグ	A	約260g	
○ R2-632	200V		2A	BL	60	45	51	80	70				4×7		ラグ	A	約440g	
○ R2-633	0		3A	BL	69	50	59	91	80				4.5×6		ラグ	A	約740g	
◎ R2-1203	220V 200V 0	12V-10V-0	0.3A	BL	43	36	35	60	52				3.8×4		ラグ	A	約160g	
○ R2-1205		12V	0.5A	BL	51	40	41	70	60				4×6		ラグ	A	約260g	
○ R2-121		10V	1A	BL	60	45	51	84	71				4×6		ラグ	A	約440g	
○ R2-122		8V	2A	BL	69	55	59	91	80				4.5×6		ラグ	A	約770g	
○ R2-123		6V	3A	BL	79	65	67	104	92				4.5×8		ラグ	A	約1.2kg	
○ R2-125		0	5A	BL	79	75	67	104	92				4.5×7		ラグ	A	約1.6kg	
○ R2-2005		220V	20V	0.5A	BL	60	45	51	80	70				4×6		ラグ	A	約440g
○ R2-201	200V 0	18V	1A	BL	69	55	59	91	80				4.5×6		ラグ	A	約770g	
○ R2-202		16V	2A	BL	79	65	67	104	92				4.5×8		ラグ	A	約1.2kg	
○ R2-203		14V	3A	BL	79	75	67	104	92				4.5×7		ラグ	A	約1.6kg	
○ R2-205		0	5A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg		
◎ R2-2403		220V	24V	0.3A	BL	50	42	43	71	60				4×6		ラグ	A	約300g
○ R2-2405	200V 0	20V	0.5A	BL	60	53	51	84	70				4×6		ラグ	A	約500g	
○ R2-241		15V	1A	BL	69	59	59	91	80				4.5×6		ラグ	A	約900g	
○ R2-242		12V	2A	BL	79	72	67	104	92				4.5×6		ラグ	A	約1.4kg	
○ R2-243		0	3A	BL	89	77	76	115	102				4.5×6		ラグ	A	約2.0kg	
○ R2-245			5A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg		

R2 200-220V-15~50V

○ R2-301	220V 200V 0	30V	1A	BL	69	65	60	94	80				4.5×6		ラグ	A	約1.0kg	
○ R2-302		25V	2A	BL	79	75	67	104	92				4.5×7		ラグ	A	約1.6kg	
○ R2-303	0	20V	3A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg		
○ R2-305		15V	5A	SS	96	92	82		59	67	40	5.5×10	4	ラグ	A	約2.9kg		
○ R2-381		38V	1A	BL	79	65	67	104	92				4.5×8		ラグ	A	約1.2kg	
○ R2-382	200V 0	35V	2A	BL	89	77	76	115	102				4×8		ラグ	A	約2kg	
○ R2-383		32V	3A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg		
○ R2-385		24V	5A	SS	108	102	99		75	73	48	6×10	4	ラグ	A	約3.9kg		
○ R2-5005	220V 200V 0	50V	0.5A	BL	69	55	59	91	80				4.5×6		ラグ	A	約770g	
○ R2-501		45V	1A	BL	79	70	67	104	92				4.5×6		ラグ	A	約1.4kg	
○ R2-502		40V	2A	SS	96	85	82		59	60	40	5.5×10	4	ラグ	A	約2.5kg		
○ R2-503		35V	3A	SS	96	95	82		59	67	40	5.5×10	4	ラグ	A	約2.8kg		
○ R2-505		0	5A	UP	128	105	131		97	60	68	6.5×12	5	M4	A	約4.8kg		

◎ 在庫品 ○ 非在庫品 無印 受注生産品

形状・寸法図

BL形 (ラグ端子板)

SS形 (ラグ端子板)

UP形 (ねじアップ式端子台)

